



## HTML 5 NEW TAG

### TAG NOT SUPPORTED IN HTML 5

<!--...-->	Define a comment
<!DOCTYPE>	Defines the document type
<a>	Defines a hyperlink href, hreflang, media, ping , rel, target, type
<abbr>	Defines an abbreviation
<acronym>	Used to define an embedded acronyms
<address>	Defines an address element
<applet>	Used to define an embedded applet
<area>	Defines an area inside an image map alt, coords, href, hreflang, media, ping, rel, shape, target, type
<article>	Defines an article cite, pubdate
<aside>	Defines content aside from the page content
<audio>	Defines sound content autobuffer, autoplay, controls, src
<b>	Defines bold text
<base>	Defines a base URL for all the links in a page href, target
<basefont>	Used to define a default font-color, font-size, or font-family for all the document
<bdo>	Defines the direction of text display dir
<big>	Used to make text bigger
<blockquote>	Defines a long quotation cite
<body>	Defines the body element
 	Inserts a single line break
<button>	Defines a push button autofocus, disabled, form, formaction, formenctype, formmethod, formnovalidate, formtarget, name, type, value
<canvas>	Defines graphics height, width
<caption>	Defines a table caption
<center>	Used to center align text and content
<cite>	Defines a citation
<code>	Defines computer code text autobuffer, autoplay, controls, src
<col>	Defines attributes for table columns
<colgroup>	Defines groups of table columns span
<command>	Defines a command button checked, disabled, icon, label, radiogroup, type

■ <datalist>	Defines a dropdown list
<dd>	Defines a definition description
<del>	Defines deleted text cite, datetime
■ <details>	Defines details of an element open
<dialog>	Defines a dialog (conversation)
<dfn>	Defines a definition term
<dir>	Used to define a directory list
<div>	Defines a section in a document
<dl>	Defines a definition list
<dt>	Defines a definition term
<em>	Defines emphasized text
<embed>	Defines external interactive content or plugin height, src, type, width
<fieldset>	Defines a fieldset disabled, form, name
■ <figure>	Defines a group of media content, and their caption
<font>	Used to define font face, font size, and font color of text
■ <footer>	Defines a footer for a section or page
<form>	Defines a form accept-charset, action, autocomplete, enctype, method, name, novalidate, target
<frame>	Used to define one particular window (frame) within a frameset
<frameset>	Used to define a frameset, which organized multiple windows (frames)
<h1> to <h6>	Defines header 1 to header 6
<head>	Defines information about the document
■ <header>	Defines a header for a section or page
<hgroup>	Defines information about a section in a document
<hr>	Defines a horizontal rule
<html>	Defines an html document manifest, xmlns
<i>	Defines italic text
<iframe>	Defines an inline sub window height, name, sandbox, seamless, src, width
<img>	Defines an image alt, src, height, ismap, usemap, width
<input>	Defines an input field accept, alt, autocomplete, autofocus, checked, disabled, form, formaction, formenctype, formmethod, formnovalidate, formtarget, height, list, max, maxlength, min, multiple, name, pattern, placeholder, readonly, required, size, src, step, type, value, width
<ins>	Defines inserted text cite, datetime
■ <keygen>	Defines a generated key in a form autofocus, challenge, disabled, form, keytype, name
<kbd>	Defines keyboard text
<label>	Defines an inline sub window for, form
<legend>	Defines a title in afieldset
<li>	Defines a list item value
<link>	Defines a resource reference href, hreflang, media, rel, sizes, type
<map>	Defines an image map name
■ <mark>	Defines marked text
<menu>	Defines a menu list label, type
<meta>	Defines meta information charset, content, http-equiv, name
<meter>	Defines measurement within a predefined range high, low, max, min, optimum, value
<nav>	Defines navigation links
<noframes>	Used to display text for browsers that do not handle frames
<noscript>	Defines a noscript section
<object>	Defines an embedded object data, form, height, name, type, usemap, width
<ol>	Defines an ordered list reversed, start
<optgroup>	Defines an option group label, disabled
<option>	Defines an option in a drop-down list disabled, label, selected, value
■ <output>	Defines some types of output for, form, name
<p>	Defines a paragraph
<param>	Defines a parameter for an object name, value
<pre>	Defines preformatted text
<progress>	Defines progress of a task of any kind max, value
<q>	Defines a short quotation cite
■ <rp>	Used in ruby annotations to define what to show browsers that do not support the ruby element
<rt>	Defines explanation to ruby annotations
<ruby>	Defines ruby annotations
<s>, <strike>	Used to define strikethrough text.
<samp>	Defines sample computer code
<script>	Defines a definition list async, type charset defer, src
■ <section>	Defines a section cite
<select>	Defines a selectable list autofocus, disabled, form, multiple, name, size
<small>	Defines small text
■ <source>	Defines media resources media, src, type
<span>	Defines a section in a document
<strong>	Defines strong text
<style>	Defines a style definition type, media, scoped
<sub>, <sup>	Defines sub/super-scripted text
<table>	Defines a table summary
<tbody>	Defines a table body summary
<td>	Defines a table cell colspan, headers, rowspan
<td>	Defines a text area
<textarea>	Defines a table footer / head autofocus, cols, disabled, form, maxlen, name, placeholder, readonly, readonly, required, rows, wrap
<tfoot>, <thead>	Defines a table footer / head
<th>	Defines a table header colspan, headers, rowspan, scope
<time>	Defines a date/tim datetime
<title>	Defines the document title
<tr>	Defines a table row datetime
<tt>	Used to define teletype text
<u>	Used to define underlined text
<ul>	Defines an unordered list
<var>	Defines a variable
■ <video>	Defines a video autobuffer, autoplay, controls, height, loop, src, width

**HTML5 TAG CHEAT SHEET**  
Created by [WebsiteSetup.org](http://WebsiteSetup.org)